Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Cairo New Cube LED Wall LED 5 W

Supplier's address: Cairo Einkauf, Werner Heisenberg Str. 14, 64823 Gross Umstadt, DE

Model identifier: EU1479BE-5R-07 + EU1479BE-89-07

Type of	light	source:	
---------	-------	---------	--

Type of light source:						
Lighting technol	ogy used:	LED	Non-directional or directional:	NDLS		
Light source cap	-type	Not applicable				
(or other electri	(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:		Nein	Envelope:	-		
High luminance	High luminance light source:					
Anti-glare shield	l:	Nein	Dimmable:	Yes		
		Product para	meters			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consun mode (kWh/100 up to the neares	00 h), rounded	6	Energy efficiency class	E		
Useful luminou indicating if it re in a sphere (36 cone (120º) or in (90º)	efers to the flux 50º), in a wide	690 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	<u>-</u>		
On-mode p expressed in W	ower (P _{on}),	5,6	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93		
Outer	Height	70	Spectral power	See image		
dimensions	Width	100	distribution in the	in last page		
without	Depth	100		Soite 1 / 2		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity	0,435		
		coordinates (x and y)	0,402		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	66	Survival factor	1,00		
the lumen maintenance factor	0,97				

(a)'-': not applicable; (b)'-': not applicable;