Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Cairo LED-Wandleuchte Mosta 18W

Supplier's address: Cairo Einkauf, Werner Heisenberg Str. 14, 64823 Gross Umstadt, DE

Model identifier: EU1604AD-5R-17 + EU1604AD-4S-17

Type	of light	source:
------	----------	---------

Type of light source:						
Lighting technol	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap	o-type	Not applicable				
(or other electri	(or other electric interface)					
Mains or non-m	nains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable	e light source:	Nein	Envelope:	-		
High luminance	light source:	Nein				
Anti-glare shield	d:	Nein	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
	mption in on- 100 h), rounded st integer	18	Energy efficiency class	F		
indicating if it re in a sphere (3)	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	-		
On-mode pexpressed in W	oower (P _{on}),	17,1	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93		
Outer	Height	80	Spectral power	See image		
dimensions	Width	220	distribution in the	in last page		
without	Depth	102		Soite 1 / 2		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity	0,435		
		coordinates (x and y)	0,402		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	60	Survival factor	1,00		
the lumen maintenance factor	0,97				

(a)'-': not applicable; (b)'-': not applicable;